



DL-200

Indispensable in many places



HIGHLIGHTS AT A GLANCE:

- Easy and Quick media loading
- Variety of interfaces
- Supports ZPL and EPL emulation
- • Small footprint

DL-200

Tally Dascom's DL-200 thermal transfer printer offers reliability, precision and performance in a compact size.

The user friendly design of the printer allows a space saving vertical opening and an easy to use print mechanism ensures quick media and ribbon loading.

The DL-200 is easily integrated into existing systems as there are several interfaces also available. In addition to this, the DL-200 is also available with an optional cutter.

TECHNICAL DATA

Print Speed	5 ips (127 mm/Sek.)
Print Width	4" (108 mm)
Print Method	Direct Thermal or Thermal Transfer
Resolution	203 dpi
Fonts	Font A - Font V (ZPL) User defined fonts can be downloaded into FLASH/SDRAM
Print head Lifetime	30 km or 6 months
Memory	8 MB Flash, 8 MB SDRAM
Interfaces Standard	USB (2.0 Full Speed)
Interfaces Optional	Serial (RS-232C), Parallel (IEEE 1284), Ethernet (10/100)
Emulations	ZPL II, EPL
Consumables	Ribbon, Direct Thermal/ Thermal Transfer paper and labels
Ribbon	Width: 30 - 110 mm; Length: 74 m Core diameter: 0,5" (12,7 mm); Outside diameter: 37 mm
Media	Width: 25 - 120 mm; Thickness: 0,05 - 0,32 mm Core diameter: 1" or 1,5" (25,4 mm or 37 mm); Outside diameter: 5" (127 mm)
Sensors	Black Mark, Label Gap, Ribbon
Barcode	1D: Code 11, Interleaved 2-of-5, Code 39, Code 49, Code 93, Code 128, Planet Code, EAN 8, EAN 13, UPC-E, UPC-A, Industrial 2 of 5, Standard 2 of 5, Codabar, MSI, Plessey 2D: PDF 417, MaxiCode, QR Code, Data Matrix
Physical Weight	1,8 kg
Physical Size	207 x 241 x 172 mm (W x D x H)
Power Voltage	100 - 240 V AC - 50/60 Hz
Temperature	+5° to +40° C
Humidity	10% to 98% (non condensing)
Print Volume	up to 300 m/day
Printer Driver	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022
Options	Models with cutter or peeler; Serial, Parallel, Ethernet interface

Configurations:

- **DL-200** Standard Product (USB only)
- **DL-200 Ser** Model with USB & ser. interface
- **DL-200 Par** Model with USB & par. interface
- **DL-200 Eth** Model with USB & Ethernet interface

DASCOM GB Ltd

Hart House, Priestley Road
Basingstoke | Hampshire RG24 9PU | ENGLAND
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400
info.gb@dascom-com | www.dascom.co.uk

DASCOM Europe GmbH

Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.

R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047